


Verification



Face



Fingerprint



Card



Password



QR

Features



Mask
Detection



Live
Detection



Cloud



WDR



Touch Screen



Wi-Fi



TCP/IP



MultiFace



TrueFace Recognition Device

TrueFace3000FP

- 4.3 inch glass touch screen with a resolution of 480 × 272.
- 2-MP wide-angle dual-lens camera with IR illumination and DWDR.
- Multiple unlock methods including Face, Fingerprint, Password, Card and QR. You can also combine them to create your own personal unlock methods.
- Supports mask detection.
- Supports visitor QR code.
- Recognizes faces 0.3 m to 1.5 m away (0.98 ft-4.92 ft).
- Supports 5,000 users, 5,000 faces, 5,000 Fingerprints, 5,000 passwords, 5,000 cards, and 300,000 records.
- Liveness detection has a face recognition accuracy rate of 99.9% and the 1:N comparison time is 0.2 s per person.
- Supports customization of voice prompts.


Specification

Capacity	
User Capacity	5,000
Face Capacity	5,000
Fingerprint Capacity	5,000
Password Capacity	5,000
Card Capacity	5,000
QR Capacity	5,000
Log Capacity	3,00,000
System	
Main Processor	Embedded Processor
Operating System	Linux
Network Protocol	IPv4;RTSP;RTP;TCP;UDP;SIP;P2P
OSDP Protocol	Yes
Interoperability	ONVIF;CGI
SDK and API	Yes
Basic	
Product Type	Standalone
Display Screen	4.3" LCD
Screen Type	Capacitive Touchscreen
Screen Resolution	480 (H) × 272 (V)
Camera	2-MP CMOS HD dual-lens camera
WDR	DWDR
Light Compensation	Auto IR
Voice Prompt	Yes
Casing	PC + ABS
Function	
Unlock Mode	Face, Fingerprint, Password, Card and QR
Card Type	MIFARE Card
Period eList	128 periods
Holiday Period	128 periods
Network Update	Yes
First User Unlock	Yes
Remote Verification	Yes
Restricted List/Trusted List	Yes
Wi-Fi	Yes

Peripheral Card Reader	1 × RS-485 card reader; 1 × Wiegand card reader
Multi-user Authentication	Yes
Real-time Monitoring	Yes
Web Configuration	Yes
Auto Registration	Yes
Performance	
Card Reading Distance	0 cm–3 cm (0"–1.18")
Face Recognition Height Range	1.1 m– 2.0 m (3.61 ft–6.56 ft)
Face Recognition Distance	0.3 m–1.5 m (0.98 ft–4.92 ft)
Face Recognition Accuracy	99.9%
Face Recognition Time	0.2 s
Fingerprint Recognition Time	0.2 s
Read Speed (QR Code)	500 ms
Port	
RS-485	1
Wiegand	1
USB	1 × USB 2.0
Network Port	1 × RJ-45 10/100 Mbps self-adaptive Ethernet port
Exit Button	1
Lock Control	1
Door Status Detection	1
Alarm	
Anti-pass Back	Yes
Tamper Alarm	Yes
Duress Alarm	Yes
Door Sensor Timeout	Yes
Intrusion	Yes
Illegal Card Exceeding Threshold	Yes
General	
Power Adapter	Standard
Power Supply	12 VDC, 1.5 A

Power Consumption	≤18 W
Product Dimensions	115.0mm*118.0mm*27.1mm (4.53"*4.65"*1.07") (H*W*H)
Packaging Dimensions	190mm*179mm*127mm (7.48"*4.65"*5.00") (L*W*H) Protection Box
Operating Temperature	−10 °C to +40 °C (+14 °F to +104 °F)
Operating Humidity	0%–90% (RH), non-condensing
Operating Environment	Indoor
Net Weight	250 g (0.55 lb)
Gross Weight	400 g (0.88 lb)
Accessory	Wall mount bracket (included)
Installation	Wall mount

Dimensional Drawing



Applications




Address : Building No. 7425, Secondary No. 2188
 Al Olaya Street, Al Woroud District, Riyadh-12253,
 Kingdom of Saudi Arabia


Global Presence: India (H.O), Dubai, Nigeria


Phone : +966-539157364


Sales : sales@timewatcharabia.com


Support : 011-41916615

Disclaimer : All pictures shown are for illustration purposes only. The actual product and color may vary due to product enhancement. The brief specification is mentioned and may change without prior notice. Please consult us before placing any order.